

CAMERA SPECIFICATION

Image Device	1/3" CMOS PC3089		
TV System	PAL		NTSC
Effective Pixels	756*504 pixels		
Sensing Area	4.80 mm*3.73mm		
Scanning System	2:1 Interlace		
Sync. System	Internal		
Resolution	500TV Lines		
Horizontal Sync Frequency	15.625 kHz		15.734 kHz
Vertical Sync Frequency	50 Hz		60 Hz
Video Output	1.0Vp-p, 75Ohm		
Gamma Consumption	0.45		
AGC	Auto		
S/N Ratio	Better than 46.5dB		
White Balance	Auto		
Electronic Shutter	1/60(NTSC)/1/50(PAL)~1/100,000 Seconds		
BLC	Auto		
Storage Temperature	-30°C ~ 80°C, RH95%MAX		
Operating Temperature	-20°C ~ 60°C, RH95%MAX		
Channels of frequency available:	<input type="checkbox"/> CH1	<input type="checkbox"/> CH2	<input type="checkbox"/> CH3 <input type="checkbox"/> CH4
Power Supply	DC12V		
Waterproof rating	IP69K		
Viewing Angle	120°		
Audio	Yes		
Minimum Illumination	0 Lux		
Night vision distance	12~15m		
Image mode	Mirror		
IR-CUT	Yes		